



IMPIEGO

Tubo in gomma spiraleto ondulato idoneo per aspirazione di aria e fumi industriali.

- **Temperatura:** -30°C +120°C

STRUTTURA

- **Sottostrato:** liscio in gomma nera EPDM.
- **Rinforzi:** spirale metallica incorporata con tessuti sintetici ad alta resistenza.
- **Copertura:** in gomma nera EPDM resistente agli agenti atmosferici.
- **Superficie:** ondulata ad impressione tela.

Disponibile su richiesta **AIRVENT/PA:** sottostrato in gomma para beige antiabrasiva.



APPLICATION

Hardwall corrugated cover rubber hose suitable for suction of hot air and fumes.

- **Temperature range:** -30°C +120°C

CONSTRUCTION

- **Tube:** black, smooth EPDM rubber.
- **Reinforcement:** steel wire helix and high strength synthetic textile plies.
- **Cover:** black, weathering resistant EPDM rubber.
- **Surface:** corrugated fabric finished.

Available on request **AIRVENT/PA:** beige, abrasion resistant natural rubber.

DIAMETRO INTERNO INSIDE DIAMETER		SPESSORE THICKNESS		PESO TEORICO WEIGHT		ASPIRAZ. VACUUM	RAGGIO CURVATURA BENDING RADIUS		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	mm	inch	mt	ft
30	1.3/16"	3.5	0.14"	0.40	0.27	0.6	120	4.72"	40	131
32	1.1/4"	3.5	0.14"	0.45	0.30	0.6	130	5.12"	40	131
35	1.3/8"	3.5	0.14"	0.50	0.34	0.6	140	5.51"	40	131
38	1.1/2"	3.5	0.14"	0.55	0.37	0.6	150	5.91"	40	131
40	1.9/16"	3.5	0.14"	0.60	0.40	0.6	160	6.30"	40	131
45	1.3/4"	3.5	0.14"	0.70	0.47	0.6	180	7.09"	40	131
50/51	2"	3.5	0.14"	0.80	0.54	0.6	200	7.87"	40	131
60	2.3/8"	3.5	0.14"	0.95	0.64	0.6	240	9.45"	40	131
70	2.3/4"	4.5	0.18"	1.25	0.84	0.6	280	11.02"	20	65.5
75/76	3"	4.5	0.18"	1.30	0.87	0.6	300	11.81"	20	65.5
80	3.5/32"	4.5	0.18"	1.40	0.94	0.6	320	12.60"	20	65.5
90	3.17/32"	4.5	0.18"	1.55	1.04	0.6	360	14.17"	20	65.5
100/102	4"	4.5	0.18"	1.70	1.14	0.6	400	15.75"	20	65.5